

UltraSpeed™ UPS-able Quad PowerLine NetBridge™

APL4200-200™



200Mbps UltraSpeed™ UPS Power Ready Ethernet Bridge

FEATURES & BENEFITS

- Uninterruptible PowerLine networking during facility power outage while UPS sustaining computer and peripheral devices operation
- Four RJ-45 MDI/MDIX auto detection Ethernet ports
- Four power outlets with high surge protect capability (1400 Joules) with UPS power pass through support
- 10A Over Current/Circuit Short Protection to protect both attached equipments and the UPS source
- Up to 200Mbps speed over the standard facility electrical power lines
- Integrated Quality of Service (QOS) for ensure the connection reliability
- Transparent to facility circuit breakers
- Simple Plug-and-Play installation
- Supports up to sixteen APL4200-200 devices on one network domain
- 168-bit Tri-DES encryption for data transmission security
- Network segmentation through network identifier
- Ident-and-Connect™ feature allows ease of network scan and network segmentation
- Web based configuration
- Up to 300 meters of operational distance
- Compliance with IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, UPA

OVERVIEW

The patent pending Aboundi APL4200-200 UltraSpeed™ Series UPS-able Quad PowerLine Ethernet NetBridge™ allows the Plug-and-Play simplicity with continuous networking connectivity even during power outage by utilizing the existing UPS system to facilitate network powering support. The APL4200-200 enables IP Camera, Video Server, POS machine, Media Converter, Printers, Digital Signage and Network Equipments for easy Local Area Networking (LAN) and broadband access in a tight clustered space with its 200Mbps high bandwidth.

The APL4200-200 NetBridge™ can be quickly installed for commercial applications where small to medium sized networking group requires UPS operational continuity. This networking group can be very easily reallocated without the need to rewire “home run” Ethernet drops to such cluster group locations with uninterruptible network operational reliability.

The APL4200-200 NetBridge™ is designed specifically for small cluster networking applications by providing four MDI/MDIX auto detection RJ-45 ports that can be connected to any 10/100Mbps Ethernet ports on computers and other peripheral devices. The build-in four noise filtered and surge protected AC power plugs not only provides UPS pass through support but also with short circuit protection to the UPS source.



UltraSpeed™ UPS-able Quad PowerLine NetBridge™

APL4200-200™

SPECIFICATIONS*

Compliance:

- IEEE802.3 10BASE-T
- IEEE802.3u 100BASE-TX
- UPA

Frequency Band:

- 2MHz ~ 30MHz

Interface:

- Four RJ-45 Connectors
- 200Mbps PowerLine connectivity
- Integrated four noise filtered and surge protected AC Power Outlets

Access Methods:

- CSMA, TDMA

Encryption:

- 168-bit Tri-DES algorithm

Security:

- VLAN

QOS:

- VLAN IEEE 802.1 p/q

Nodes:

- Supports up to sixteen APL4200-200 per network domain

Mechanical:

- W x D x H : 120 x 235 x 40 mm/ 4.72 x 9.25 x 1.57 in
- Weight : 450g (1 lb)

LED:

- Power LED: Green
On: Power On Off: Power Off
- Status LED:
PowerLine : Green
On : Link Blink : Activity
Ethernet Ports : Green (Ports 1-4)
On : Link Blink : Activity

Environmental:

- Temperature
Operating : 0 ~ +40°C/ +32 ~ +104°F
Storage : -25 ~ +60°C/ -13 ~ +140°F
- Humidity
Operating : 10 ~ 90% RH (non-condensing)
Storage : 10 ~ 95% RH (non-condensing)

Power Supply:

- Input rating : AC110~220V, 50/60 Hz, 10A with UPS pass through
- Surge energy rating : 1400 Joules
- Over current protection : 10Amps

EMC/ Safety Certification:

- FCC Part 15, Subpart B, Class B
- UL/cUL60950-1, UL1449
- CE Class B
- CB Scheme

ORDERING INFORMATION

APL4200-200-01: 110 VAC Plug

APL4200-200-02: 220 VAC Plug

APL4200-200-03: 220 VAC UK Plug

US Patent 7,592,717

